

NETWORKTV



NetworkTV 71C 12X-USB2.0 Video Conferencing Camera

The NTV71C is a 1080p camera with 12X optical zoom and a 72.5° field of view for capturing both wide angles and for zooming into the subject showing fantastic detail. With support for full USB2.0 high speed data output, these cameras are ideal for broadcasting live high definition video signals or being utilised in video conferencing applications.

The cameras can be wall or ceiling mounted with both vertical and horizontal flip capability and come in black or white to fit the colour scheme of the room. These cameras are suitable for small, medium or large room set-ups.



Be seen in 1080p

Crystal clear High Definition 1080p video with lossless 12X optical zoom letting you get up close to see and interact with your team. The camera offers a choice of output in 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60, 720p/50




Easy Set Up - Plug & Play

With this camera you are getting the easiest solution possible. Just connect the camera and you're ready to go.



Robust Installation Options

Easily invert the camera image for installation on the ceiling. Or use the 1/4 20 screw to fasten the camera to a standard tri-pod or simply mount on the wall.



Wide Field of View

The NTV71U models offer a 72.5° wide field of view with the ability to zoom into a narrow 6.9 degrees.



Plug-and-Play USB Connectivity

Easily connect your camera to a PC, Mac or Chrome-Box without the need for additional software. For best results use a quad-core processor.



Camera Presets

Access camera presets with the IR remote control. Easily control your cameras pan tilt and zoom along with other fine tuning settings from your remote control.



Use your favorite software

Works with virtually every online video conferencing software with no need for additional drivers or proprietary connections.



RS-232/RS-485 Camera Control

Integrate the cameras into a larger control system such as Crestron, Extron or AMX. Even convert RS-232 to USB and control from your computer.

KEY FEATURES

- 72.5 degree wide-angle lens.
- High performance in low illumination situations.
- Full 1920 x 1080p HD Resolutions up to 30 frames per second.
- 2D and 3D noise reduction with our latest "low noise CMOS sensor".
- Wide Dynamic Range: capable of capturing all features of images when there is a strong contrast between subject and background.
- Variety of control options

WHAT'S IN THE BOX

- 12X Zoom USB2.0 Camera
- Power Adapter
- IR Remote Control
- RS-232C to RS-485 Cable
- User Manual

Camera Specification

Video System	1080p/60, 1080p/50, 1080p/30, 1080p/25, 720p/60, 720p/50, 720p/30, 720p/25
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Digital Zoom	32x (optional)
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal Angle of View	72.5° ~ 6.9°
Vertical Angle of View	44.8° ~ 3.9°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30° ~ +30°
Pan Speed Range	1.7° ~ 100°/s
Tilt Speed Range	1.7° ~ 69.9°/s
H & V Flip	Support
Image Freeze	Support
Number of Presets	255
Preset Accuracy	0.1°
Audio Interface	1-ch: 3.5mm Audio Interface, Line In
Communication Interface	1 x RS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P 1 x RS232 Out: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA network use only 1 x RS485: Share with RS232 Out, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-P
Power Jack	JEITA type (DC IN 12V)
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	12W (Max)
MTBF	>30000h
Size	128.5x118x156.2mm
Net Weight	0.91K g
SKU Number	NTV-71C-BK-G